

Quality

Diamond Paints

Tr. L.L.C



Diamond Paints

كواليتي

دايموند للاصباغ

لتجارة ش.ذ.م.م

DIAMONDBLACK BOARD

DESCRIPTION:

A Special Alkyd / Hard Resin base paint having good adhesion, high coverage, fast drying, and good scratch resistance towards slippage of chalk during writing and easily cleanable.

RECOMMENDED USE

On wood and masonry, school boards as a finish coat.

TECHNICAL DATA

Colors	Black & Green.
Finish	Matt.
Solid by Weight %	65 ± 5%
Viscosity (25°C)	7.5 - 8.5 Poise.
Specific Gravity	1.32 ± 0.05
Theoretical Spreading Rate	10 - 12 m ² /Lit.
Flash point	38°C

DRYING TIME

Touch dry	4 hrs.
Hard dry	24 hrs.
Ready to be used	After 3 days

SURFACE PREPARATION

Surface must be clean and dry.

APPLICATION DATA

Application Methods	Brush, Spray, Roller.
Thinning	White Spirits as required.
Guiding Data for Airless Spray	Nozzle Tip: 0.015" - 0.20" Nozzle Pressure: 2200 P.S.I.

Office No. 201 Bin Sougat Building, Salah Al Din Raod
+971 4 283 4012 Deira, Dubai - United Arab Emirates

info@qualitydiamond.ae
www.qualitydiamond.ae

**APPLICATION SYSTEM**

- One Coat of **DIAMOND Undercoat**.
- Two Coats of **DIAMOND Black Board**.

MISCELLANEOUS DATA

<p>STORAGE</p> <p>HANDLING</p> <p>SHELF LIFE</p> <p>SAFETY / HEALTH</p>	<p>The product must be stored according to Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.</p> <p>Handle with care, mix well before use.</p> <p>36 months, in original sealed container, with proper storage conditions.</p> <ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
---	--

Limited Guarantee: All Diamond Paints products are guaranteed for best performance; however since Diamond Paints does not control the final application of its products, nor the condition of the surfaces to which they are applied; a limited guarantee is provided. If the product does not perform as specified, Diamond Paints liability will under no circumstances exceed replacement of the product.

Disclaimer: To the best of our knowledge the information provided herein is true and accurate at the date of issuance. The company reserves the right to modify data contained herein without prior notice. Any change in data would normally be followed by issue of a new data sheet. The user should check with the nearest sales office of the company and confirm the validity of the information, prior to use of product.